



一、物品及厂商资料 PRODUCT AND COMPANY IDENTIFICATION

化学品名称: RLP30 系列微波多层粘结片

Trade name: RLP30 series microwave Multi-layer bonding sheet

化学品类别: 复合树脂类

Chemical family: Composite Resins 产品用途: 印刷线路板基材

Use of article: Printed circuit boards base material 制造商名称: 无锡睿龙新材料科技有限公司

Manufacturer name: Wuxi Relong New Material Technology Co.,Ltd 制造商地址: 江苏省无锡市滨湖区马山镇常康路 11 号

Manufacturer's address:NO.11 Chang Kang Road, Mashan Town, Binhu District, Wuxi, Jiangsu, China.

制造商应急电话: 0510-68578712-801 传真: 0510-68578717

Manufacturer emergency phone: **0510-68578712-801** Fax: **0510-68578717**

参考文献: GB/T 16483, 化学品安全技术说明书

Bibliography: GB/T 16483, Safety date sheet for chemical products-Content and order of section.

二、成分/组成信息 COMPOSITION/INFORMATION ON INGREDIENTS

组分名称 Chemical Name	CAS No.	EINECS/ELINCS	%
复合树脂 Composite Resins	NA	NA	Varies
玻璃纤维布 Fiberglass	65997-17-3	266-046-0	Varies
陶瓷填料 Ceramic Filler(Nuisance Dust)	NA	NA	Varies

三、危害识别 HAZARDS IDENTIFICATION

材料分类:

过度暴露影响: 正常处理不会产生。当切割或其他操作可能产生粉尘。超过分解温度下进行操作

EFFECTS OF OVEREXPOSURE: 时可能会产生有毒烟雾。

None are expected with normal handling. Cutting and other finishing operations may create dust. Ventilation and personnel protection should be similar to all



operations generating nuisance dust. Processing material at temperatures exceeding decomposition temperature may release toxic fumes.

吸入: INHALATION: 灰尘可引起呼吸道刺激。暴露在复合树脂分解产物下可能会引起肺部

金属或者聚合物烟尘发热。此特点类似于流感症状(发热,寒站,肌肉疼痛)

一般会持续 24h。

Dust may cause respiratory irritation. Remove to fresh air and seek medical attention if necessary. Exposure to Composite Resins decomposition products may cause symptoms of metal of Polymer Fume Fever. This is characterized by flu like symptoms (fever, chills, muscle aches) that last 24hours.

眼睛接触: 粉尘可能引起刺激。 EYE CONTACT: Dust may cause irritation.

皮肤接触: 粉尘可能会引起刺激,用肥皂和水彻底清洗。

SKIN CONTACT: Dust may cause irritation. Wash thoroughly with soap and water.

摄入: 未知

INGESTION: None known.

慢性病: 未知 CHRONIC: NE

四、急救措施 FIRST-AID MEASURES

吸入: 移至新鲜空气中。 如果症状持续, 请就医

INHALATION: Remove to fresh air. Obtain medical attention if symptoms persist.

眼睛接触: 用大量水冲洗眼睛 15-20 分钟。如果症状持续请就医

EYE CONTACT: Flush eyes with large amounts of water for 15 to 20 minutes. Obtain medical

attention if symptoms persist.

皮肤接触: 用清水和肥皂水冲洗 15 到 20 分钟,不要抓或者挠。如果症状持续请就医。

SKIN CONTACT: Immediately take off all contaminated clothing and flush area with water for 15

to 20 minutes. Obtain medical attention if symptoms persist.

摄入: 请就医。

INGESTION: Please medical attention.





五、消防措施 FIRE-FIGHTING MEASURES

闪点: 无资料 爆炸极限: LEL 无, UEL 无

FLASH POINT: NE °C (°F) Flammable Limits: LEL NA UEL NA

自然温度: 无资料 AUTOIGNITION TEMPERATURE: NE °C (°F)

灭火方法及灭火剂: 洒水√ 泡沫√ CO2√ 干粉√ 其他√ –

EXTINGUISHING MEDIA: Water Spray√ Foam √ CO₂ √ Dry Chemical√ Other √-

SPECIAL FIRE FIGHTING

Decomposition in a fire may produce toxic fumes. Firefighters should be equipped with self-contained breathing apparatus and turnout gear.

有害燃烧产物: 未知.

UNUSUAL FIRE AND EXPLOSION None known.

HAZARDS:

六、泄漏应急措施 ACCIDENTAL RELEASE MEASURES

个人防护措施: 防止火灾中有害烟雾的扩散,请佩戴合适的防护用品,不要呼吸还有粉尘的空

PERSONAL PRECAUTIONS: 气。消除火源,避免皮肤和眼睛接触。

In case of fire, toxic fumes are emitted. Wear suitable protective equipment. Do not breathe dust. Eliminate sources of ignition. Avoid contact with skin and

eyes.

环境预防措施: 避免进入地下水、地表水或者土壤

ENVIRONMENTAL PRECAUTIONS: Prevent from entering sewer system, surface water, or soil.

清除方法: 扫或铲到合适的容器里处理。避免产生有害粉尘。

CLEANING METHODS: Sweep or shovel into appropriate container for disposal. Avoid creation of

nuisance dust.

七、操作处置与储存 HANDLING AND STORAGE

操作注意事项: 穿戴合适的防护设备,参照第8部分。接触后用肥皂水和清水清洗双手。

HANDLING: Wear suitable protective equipment, refer to Section 8. Wash hands with soap

and water after contact.

储存注意事项: 保存在阴凉通风处。

STORAGE: Keep in a cool, well-ventilated area.

八、接触控制/个体防护 EXPOSURE CONTROLS/PERSONAL PROTECTION

呼吸防护: 如果机械通风不充分不足以将现场接触的浓度维持在2部分中列出的范围内,

RESPIRATORY PROTECTION: 需要佩戴满足安全标准的呼吸器。

None needed under normal conditions. If material is heated and odors are noticeable and/or irritating a respirator meeting safety standard should be

used.

通风

VENTILATION

局部: 建议会产生粉尘或者材料需要加热在 200℃ 的条件下采取,有粉尘产生的地方

LOCAL: 采取通风,遵守好的工业卫生习惯.

It is suggested that dust or materials should be heated under 200°C

conditions, where dust is produced and ventilation is adopted, and good

industrial hygiene practices are observed.



整体: 建议所有操作岗位执行

GENERAL: Recommended for all industrial operations.

个人防护

PERSONAL PROTECTION

手部: 防切割手套

HAND: Gloves to avoid skin contact if desired.

眼睛: 建议所有操作岗位佩戴有侧边的护目镜, 不要佩戴隐形眼镜

EYE: Safety glasses with side-shields are recommended in all industrial operations

None Required

其他: 区域中配备洗眼器和淋浴.

OTHER: Safety shower/eyewash in the area.

九、理化特性 PHYSICAL AND CHEMICAL PROPERTIES

粘结片

APPEARANCE: bonding sheet

气味: 无 None ODOR: 物理状态: 固体 PHYSICAL STATE: Solid 沸点(℃): 不适用 **BOILING POINT:** NA °C (°F) 熔点(℃): 不适用 MELTING POINT: 180 °C (°F) 凝固点: 不适用 FREEZING POINT: NA °C (°F) 闪点(℃): 不适用

FLASH POINT: NA °C (°F) 溶解性: 不适用 WATER SOLUBILITY: In-Soluble 蒸汽密度: 不适用 VAPOR DENSITY: NA 饱和蒸气压(kPa): 不适用 VAPOR PRESSURE: NA

相对密度: 不适用(Water = 1) SPECIFIC GRAVITY: NA (Water = 1)

分配系数: 不适用 PARTITION COEFFICIENT: NA 蒸汽速率: NA **EVAPORATION RATE:** NA 不适用 相对蒸汽密度: **RELATIVE DENSITY:** NA 粘度: 不适用 VISCOSITY: NA 不适用 自燃温度: **AUTO-IGNITION TEMPERATURE:** NA °C (°F)



分解温度: 不适用
DECOMPOSITION TEMPERATURE: NA °C (°F)
PH: 不适用
PH: NA

易燃性: 不适用 FLAMMABILITY: NA

十、稳定性和反应活性 STABILITY AND REACTIVITY

稳定性√ 不稳定 复合树脂在高于 300° 下开始缓慢的分解,在高于 350° 下开始快速分解,因

STABLE ✓ UNSTABLE 此不建议工艺在此情况下长期持续。

Composite Resins begins to decompose above 300°C and increases rapidly

not recommended.

避免接触的条件: 无资料 MATERIALS TO AVOID: NE

有害聚合: 可能会发生 不发生 ✓

HAZARDOUS POLYMERIZATION May Occur Does Not Occur √

分解产物: 可以分解: 二氧化碳、烷烃、 水。

HAZARDOUS DECOMPOSITION Decomposition may emit CO2 CH2(N) H2O.

十一、毒理学资料 TOXICOLOGICAL INFORMATION

致癌性: 玻璃纤维(连续长丝):IARC 第 3 组(未分类)。对人类致癌性)。

CARCINOGENIC STATUS: Fiberglass (continuous filament): IARC Group 3 (unclassifiable as to

carcinogenicity to humans).

生殖危害: 不适用 REPRODUCTIVE HAZARDS: NE

十二、生态学资料 ECOLOGICAL INFORMATION

生态毒性 不适用 ECOTOXICITY: NE

十三、废弃处置 DISPOSAL CONSIDERATION

物理/化学性质在处理过程中的影响: 不适用 PHYSICAL/CHEMICAL PROPERTIES NE

AFFECTING DISPOSAL:

环境毒性: 不适用 ENVIRONMENTAL TOXICITY DATA: NE

废弃处置方法: 根据可适用的当地法规进行处置

WASTE DISPOSAL METHOD: Dispose of in accordance with locallaws .

十四、运输信息 TRANSPORT INFORMATION

UN 编号: 无规定

UN NUMBER: Not Regulated

包装类别: 无规定

PACKING GROUP: Not Regulated



危险等级(ES): 无规定

HAZARD CLASS (ES): Not Regulated

环境危害: 不适用 ENVIRONMENTAL HAZARDS: NE

十五、法规信息 REGULATORY INFORMATION

国际法规:

INTERNATIONAL REGULATIONS:

The United States(TSCA)

All materials are listed or exempt from TSCA listing.

加拿大 (DSL/NDSL): 豁免物质

Canadian (DSL/NDSL): Article - exempt

澳大利亚 (ACIS): 豁免物质

Australian (ACIS): Article - exempt

韩国 (KECI): 豁免物质

Korea (KECI): Article - exempt

日本 (ENCS, MITI): 豁免物质

Japan (ENCS, MITI): Article - exempt

欧盟指示 2011/65/EC (RoHS): 不含任何故意添加 RoHS 指令所提到的物质

EU Directive 2011/65 / EC (RoHS): It does not contain any intentional addition of the substances mentioned in the

RoHS Directive

十六、其它信息 OTHER INFORMATION

NA =不适用

NA = Not Applicable

NE =未建立

NE = Not Established

NC =未分类

NC = Not Classified

制作: 石秀芳 审核: 张中华

PREPARED BY: Xiufang Shi REVIEWED BY: Zhonghua Zhang

制作日期: 2019/8/6

Date Prepared: 8/6/2019

本表所含的信息来源于我们认为准确的数据,但是未提供有关数据准确性或相关使用结果的明确或暗示性的保证。

睿龙公司对于由本材料导致购买方,用户或第三方所发生的人生伤害或财产损失不承担任何责任。相关材料使用的风险则由购买方或 用户承扣。

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED ACCURATE. HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THESE DATA OR THE RESULT TO BE OBTAINED FROM THE USE THEREOF.

RELONG CORPORATION ASSUMES NO RESPONSIBILITY FOR PERSONAL INJURY OR PROPERTY DAMAGE TO VENDEES, USERS OR THIRD PARTIES CAUSED BY THE MATERIAL. SUCH VENDEES OR USERS ASSUME ALL RISKS ASSOCIATED WITH THE USE OF THE MATERIAL.